EC-3, 07 FEB 2013 to 07 MAR 2013

## ACITO ONE DEPARTURE (RNAV) CHICAGO, ILLINOIS 1180 1180 135.4 282.255 1180 1180 **GND CON** 121.75 (Outbound) 1180 124.125 (TWR NORTH) 1180 O'HARE TOWERS 128.15 (Rwy 9L/27R) 120.75 126.9(CENTER) 132.7 348.0(CENTER) 273° CHICAGO DEP CON SOUTH 1180 126.625 269.5 1180 1180 1180 1180 TAKEOFF MINIMUMS: AHLOU Standard with minimum climb of 547' per NM to Rwys 4L 3000, then minimum climb of 350' per NM to 4000. Standard with minimum climb of 690' per NM to Rwys 4R: 3000, then minimum climb of 350' per NM to 4000. Rwys 9L Standard with minimum climb of 570' per NM to 3000, then minimum climb of 350' per NM to 4000. Standard with minimum climb of 541' per NM to Rwys 9R: 3000, then minimum climb of 350' per NM to 4000. Standard with minimum climb of 672' per NM to Rwys 10: 3000, then minimum climb of 350' per NM to 4000. Rwys 14L: Standard with minimum climb of 547' per NM to 3000, then minimum climb of 350' per NM to 4000. **ADELL** Rwys 14R: Standard with minimum climb of 670' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwys 22L: Standard with minimum climb of 807' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwys 22R: Standard with minimum climb of 521' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwy 27L: Standard with minimum climb of 532' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwy 27R: Standard with minimum climb of 631' per NM to 3000, then minimum climb of 350' per NM to 4000. Rwy 28: Standard with minimum climb of 685' per NM to 3000, then minimum climb of 350' per NM to 4000. Standard with minimum climb of 631' per NM to **AKMIE** 3000, then minimum climb of 350' per NM to 4000. Rwys 32R: Standard with minimum climb of 587' per NM to 3000, then minimum climb of 350' per NM to 4000. NOTE: TURBOJET departures maintain 250 KIAS until advised by ATC. NOTE: If unable to accept climb gradient, advise ATC as soon as possible prior to departure. NOTE: DME/DME/IRU or GPS Required. NOTE: RNAV 1 NOTE: RADAR Required. NOTE: AKMIE TRANSITION: For aircraft inbound to BMI, SPI or PIA, or as assigned by ATC. **ARLYN** (NARRATIVE ON FOLLOWING PAGE) NOTE: Chart not to scale.