


HELENA TOWER ★
118.3 (CTAF) 257.8
HELENA DEP CON ★
119.5 229.4
SALT LAKE CENTER
133.4 285.4



HELENA	
117.7 HLN	⋮⋮⋮
Chan 124	
N46° 36.41' - W111° 57.21'	
L-13, H-1	

TAKE-OFF MINIMUMS

- Rwy 5: Standard with minimum climb of 250 feet per NM to 8100.
- Rwy 9: Standard with minimum climb of 240 feet per NM to 8100.
- Rwys 16, 23: NA- obstacles.
- Rwy 27: Standard with minimum climb of 390 feet per NM to 8100.
- Rwy 34: NA- ATC.

TAKE-OFF OBSTACLE NOTES

- Rwy 5: Ground beginning 5' from DER, 495' right of centerline, up to 3826' MSL.
Fence beginning 423' from DER, 331' right of centerline, up to 10' AGL/ 3832' MSL.
- Rwy 27: Building 1593' from DER, 731' left of centerline, 58' AGL/ 6385' MSL.
Ground beginning 101' from DER, 346' left of centerline, up to 3871' MSL.
Tree 1567' from DER, 616' left of centerline, 47' AGL/ 3906' MSL.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAY 5: Climbing left turn heading 310° to intercept HLN VORTAC R-336 to 8100', then climbing left turn to 9000' via HLN VORTAC R-336 to HLN VORTAC.

TAKE-OFF RUNWAY 9: Climbing left turn heading 307° to intercept HLN VORTAC R-336 to 8100', then climbing left turn to 9000' via HLN VORTAC R-336 to HLN VORTAC.

TAKE-OFF RUNWAY 27: Climbing right turn heading 006° to intercept HLN VORTAC R-336 to 8100', then climbing left turn to 9000' via HLN VORTAC R-336 to HLN VORTAC.

NW-1, 07 FEB 2013 to 07 MAR 2013

NW-1, 07 FEB 2013 to 07 MAR 2013