

(INDY4.VHP) 12264
INDY FOUR DEPARTURE

SL-203 (FAA)

INDIANAPOLIS INTL (IND)
 INDIANAPOLIS, INDIANA

ATIS 134.25
 CLNC DEL
 128.75 257.8
 GND CON
 121.9 257.8
 INDY TOWER
 120.9 257.8
 INDIANAPOLIS DEP CON
 119.05 317.8 (WEST)
 124.95 317.8 (EAST)

BOILER
 115.1 BVT
 Chan 98
 N40°33.37' - W87°04.16'
 L-27, H-5-10

MARION
 108.6 MZZ
 Chan 23
 N40°29.60' - W85°40.75'
 L-27

ROSEWOOD
 117.5 ROD
 Chan 122
 N40°17.27' - W84°02.59'
 L-27, H-10

MUNCIE
 114.4 MIE
 Chan 91
 N40°14.24' - W85°23.64'
 L-27

CHAMPAIGN
 110.0 CMI
 Chan 37
 N40°02.07' - W88°16.56'
 L-27

KOKOMO
 113.5 OKK
 Chan 82
 N40°31.67' - W86°03.48'
 L-27, H-5-10

DAYTON
 114.5 DQN
 Chan 92
 N40°00.99' - W84°23.81'
 L-27, H-10

LOCALIZER
 111.75 I-UZK
 Chan 54(Y)

RICHMOND
 110.6 RID
 Chan 43
 N39°45.30' - W84°50.33'
 L-27, H-10

BRICKYARD
 116.3 VHP
 Chan 110
 N39°48.88' - W86°22.05'
 L-27, H-5-10


LOCALIZER
 111.15 I-OQV
 Chan 48(Y)

TERRE HAUTE
 115.3 TTH
 Chan 100
 N39°29.34' - W87°14.94'
 L-27, H-5

LOCALIZER
 111.15 I-FVJ
 Chan 48(Y)

SHELBYVILLE
 112.0 SHB
 Chan 57
 N39°37.95' - W85°49.46'
 L-27, H-5-10

HOOSIER
 110.2 OOM
 Chan 39
 N39°08.63' - W86°36.78'
 L-27



POCKET CITY
 113.3 PXV
 Chan 80
 N37°55.70' - W87°45.74'
 L-16, H-5

NOTE: RADAR Required.
 NOTE: Turbojets accelerate to 250K until reaching 10000, if unable advise ATC.
 NOTE: Select appropriate localizer/DME frequency/channel prior to departure.

TAKE-OFF MINIMUMS:
 Rwy's 5L, 5R, 14, 23L, 23R, 32 Standard

((NARRATIVE ON FOLLOWING PAGE))

NOTE: Chart not to scale

(INDY4.VHP) 12264
INDY FOUR DEPARTURE

INDIANAPOLIS, INDIANA
 INDIANAPOLIS INTL (IND)

EC-2, 07 FEB 2013 to 07 MAR 2013

EC-2, 07 FEB 2013 to 07 MAR 2013