

MIDLAND FIVE DEPARTURE

SL-258 (FAA)

MIDLAND INTL (MAF)
MIDLAND, TEXAS

ATIS 126.8 235.975
MIDLAND CLNC DEL
118.05 317.65
MIDLAND GND CON
121.9 348.6
MIDLAND DEP CON
124.6 290.4
MIDLAND TOWER *
118.7 273.45

LUBBOCK
109.2 LBB
Chan 29
N33°42.30'-W101°54.84'
L-6, H-6

WICHITA FALLS
112.7 SPS
Chan 74
N33°59.24'-W98°35.61'
L-17, H-6

CHISUM
116.1 CME
Chan 108
N33°20.25'-W104°37.27'
L-6, H-6

BIG SPRING
114.3 BGS
Chan 90
N32°23.14'-W101°29.02'
L-6, H-6

ABILENE
113.7 ABI
Chan 84
N32°28.88'-W99°51.81'
L-17, H-6

HOBBS
111.0 HOB
Chan 47
N32°38.29'-W103°16.16'
L-6


MIDLAND
114.8 MAF
Chan 95
N32°00.56'-W102°11.42'
L-6

TUSCOLA
111.6 TQA
Chan 53
N32°14.14'-W99°49.01'
L-17, H-6

CARLSBAD
116.3 CNM
Chan 110
N32°15.40'-W104°13.56'
L-6

GLEN ROSE
115.0 JEN
Chan 97
N32°09.58'-W97°52.66'
L-17, H-6

WINK
112.1 INK
Chan 58
N31°52.49'-W103°14.63'
L-6, H-6



SAN ANGELO
115.1 SJT
Chan 98
N31°22.50'-W100°27.29'
L-19, H-6

PECOS
111.8 PEQ
Chan 55
N31°28.16'-W103°34.49'
L-6, H-6

FORT STOCKTON
116.9 FST
Chan 116
N30°57.13'-W102°58.54'
L-19, H-6

JUNCTION
116.0 JCT
Chan 107
N30°35.88'-W99°49.05'
L-19, H-7

TAKEOFF MINIMUMS

Rwys 4, 10, 16L, 16R, 22, 28: Standard.
Rwy 34L: 300-1½ or standard with minimum climb of 400' per NM to 3200.
Rwy 34R: 300-1¼ or standard with minimum climb of 320' per NM to 3200.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SC-3, 07 FEB 2013 to 07 MAR 2013

SC-3, 07 FEB 2013 to 07 MAR 2013

DEPARTURE ROUTE DESCRIPTION

- TAKEOFF RWY 4:** Climb heading 045°, maintain 13000 (or lower filed altitude). Thence...
- TAKEOFF RWY 10:** Climb heading 105°, maintain 13000 (or lower filed altitude). Thence...
- TAKEOFF RWY 16L:** Climb heading 168°, maintain 13000 (or lower filed altitude). Thence...
- TAKEOFF RWY 16R:** Climb heading 166°, maintain 13000 (or lower filed altitude). Thence...
- TAKEOFF RWY 22:** Climb heading 225°, maintain 13000 (or lower filed altitude). Thence...
- TAKEOFF RWY 28:** Climb heading 285°, maintain 13000 (or lower filed altitude). Thence...
- TAKEOFF RWY 34L:** Climb heading 346°, maintain 13000 (or lower filed altitude). Thence...
- TAKEOFF RWY 34R:** Climb heading 348°, maintain 13000 (or lower filed altitude). Thence...

...Expect vectors to assigned route/fix. Expect clearance to filed altitude/flight level ten (10) minutes after departure.

MIDLAND FIVE DEPARTURE